

TRIAX FLEET EURO LSAP

ULTRA HIGH PERFORMANCE FULL SYNTHETIC EURO VI LSAP ENGINE OIL FOR EUROPEAN TRUCKS

TRIAX FLEET EURO LSAP is a ultra-high performance full synthetic engine oil line designed for Euro 5 and Euro 6 heavy duty European and North American diesel engines. This product features top of the line base oils, coupled with next generation additive system designed to provide optimal performance in heavy duty severe service applications.

TRIAX FLEET EURO is a low SAPS Lubricant reinforced with TRIAX proprietary molybdenum and boron friction modification and optimization technology, as well as the most advanced detergent and viscosity stabilization technology. TRIAX unique additive packs ensure top performance at the quality criterions wear protection and friction reduction, detergency & dispersancy, corrosion prevention, viscosity temperature dependency, thermal oxidative stability, low evaporation tendency, good elastomer compatibility and almost no environmental impact.

PERFORMANCE

- Up to 53% Better engine wear protection. Exceeds ACEA, MAN and MB specifications for wear and cleanliness.
- Over 75% better Oxidation control compared to standard API CJ-4 Limits
- Friction modified and optimized using organic Borate and Molybdenum CRP Technology
- Extreme oxidation stability ensures very long oil life and prevent oil oxidative thickening and premature wear
- High retention TBN with extremely slow degradation, lasts 40% longer than regular TBN additives ensuring long term corrosion protection
- Next generation detergent system to keep engines clean and prevent soot / ash damage to pistons and rings
- 2% fuel economy vs 15W-40 and other 10W-40 viscosity grades and up to 6% for 5W-30 viscosity
- Drain interval 150,000 km for European Euro 6 and Euro 5 trucks, 100,000 km for others* (with oil analysis recommended)
- Superior viscosity and shear stability to support long term prevention of viscosity loss

PERFORMANCE HIGHLIGHTS



UP TO 100,000 MILES PROTECTION

For highway trucks



UP TO 25,000 MILES PROTECTION

For diesel pick-up trucks

The above drain intervals reflect the capability of the product, taking into consideration mechanically sound engines and good maintenance practices. Always use oil analysis as engine blow by, coolant leaks and other oil contamination can happen at any time and directly affect the longevity of engine oils.

3-6% FUEL ECONOMY
for heavy duty trucks

**EXCEPTIONAL OXIDATION
STABILITY**

HIGH TBN
for exceptional acid control

SPECIFICATIONS & APPLICATIONS

TRIAX FLEET EURO LSAP products are especially designed for UHPD Euro 5 and Euro 6 engines fitted on European heavy duty highway trucks and buses fitted with the latest emission control systems such as DPF (Diesel Particulate Filters), DOC (Diesel Oxidation Catalyst), SCR (Selective Catalytic Reduction) equipment. This product is fully backwards compatible with previous European Euro 2,3 and 4 engines for mixed fleet operations and exceeds latest requirements for Mercedes Benz, VOLVO, DAF, IVECO and many other OEMs.

TRIAX FLEET EURO LSAP is also recommended for CNG (Compressed Natural Gas) engines from MAN, VOLVO, SCANIA, IVECO, DAF, MERCEDES BENZ.

SPECIFICATION COVERAGE: These products meet or exceed the following API and OEM specifications.

- API: CJ-4, CI-4, CH-4
- ACEA: E6,E9
- Caterpillar: ECF-3
- Cummins: CES 20081
- DAF & DAF Long Drain
- Deutz: DQC IV-10 LA
- IVECO: NG 2 (meets requirements)
- JASO DH-2;
- MACK: EO-O Premium Plus
- MAN: M3477, M3271-1
- MB: 228.51, 228.31
- MTU: Category 3.1
- Renault Trucks: RLD-3
- Volvo: VDS-3 CNG, VDS-4 (Euro 6)
- Scania Low Ash, LDF-3, LDF-2

TYPICAL PROPERTIES

Parameter (test)	10W-40	5W-30
Viscosity, Kinematic cSt at 40°C	92.4	69.7
Viscosity, Kinematic cSt at 100°C	13.22	11.40
Viscosity Index (ASTM D2270)	167	163
Flash Point, °C (°F)	234 (453)	238 (460)
Pour Point, °C (°F)	-39 (-38)	-41 (-41)
CCS Viscosity @ °C, cP (ASTM D5293)	6600 (-25)	4400 (-25)
Total Base Number (ASTM D2896)	10	12
HTHS High Temp High Shear,cP (ASTM D5481)	4.2	3.62
Sulfated Ash Content % Wt. (ASTM D874)	0.22	0.25